



Art. No.	Date Publish.	Replaces sheet
7127	2015-11-18	2015-09-02

Mega Truck

DESCRIPTION

Mega Truck is a superior quality diesel engine oil for vehicles operating in heavy traffic and under demanding conditions. Mega Truck is a Super High Performance Diesel (SHPD) oil.

PROPERTIES

Mega Truck is based on high quality paraffin base oils whose natural properties are high viscosity index, high oxidation stability and excellent lubricity. Mega Truck contains carefully selected additives that keep the engine clean, minimise wear and prevent rust and corrosion. Mega Truck is ideal for harsh operating conditions.

RECOMMENDATIONS

Mega Truck is recommended for all heavy-duty vehicles with supercharged diesel engines operating under harsh conditions and/or extended oil change intervals. The oil is ideal for Euro III and IV engines. It can also be used in cars - petrol or diesel.



SPECIFICATIONS		
Analyses	Units	Results
Density at 15 °C	kg/m ³	890
Flash Point	°C	210 (ASTM D92)
Pour Point	°C	-36
Viscosity at		
40 °C	mm ² /s	105
100 °C	mm ² /s	15
Viscosity Index		135
Pumpability Limit	°C	-25
TBN	mg KOH/g	10
Ash Content	%	1.4

RECOMMENDED FOR

SAE	15W-40
API	CI-4, CH-4, SL
ACEA	E7, E5, E3, B4, B3, A3
Global	DHD-1
MB	228.3
Volvo	VDS-3
MAN	M3275
Cummins	20071/72/76/77/78
Caterpillar	ECF1/ECF2
RenautVI	RLD/RLD2
ZF TE-ML	04C/07C
MTU	Type 2
Mack	EO-M Plus
(Allison)	C4)
Meets requirements for DAF, IVECO, Scania	